# NSN 5985-01-313-3856

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-313-3856

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

## Bend Angle In Deg:

90.0 single bend e-plane

## **Tubing Wall Construction Style:**

Seamless all tubing segment

## Flange Quantity:

2

#### Flange Connecting Hole Diameter:

0.168 inches first flange all connection facilities and 0.175 inches first flange all connection facilities

## Voltage Standing Wave Ratio:

1.15

Insertion Loss In Decibels:

0.10

#### Maximum Operating Pressure:

45.0 pounds per square inch gage

## Waveguide Longer Offset Distance:

Between 1.865 inches and 1.885 inches

## Flange Connecting Facility And Quantity:

4 unthreaded hole first flange all connection facilities

# Waveguide Offset Distance:

Between 1.178 inches and 1.198 inches

## Flexibility:

Rigid third tubing segment

#### Material:

Copper alloy first tubing segment

#### **Precious Material And Location:**

Internal surfaces silver

## **Precious Material:**

Silver

#### Surface Treatment:

Paint all tubing segment and flange outside surfaces

#### **Style Designator:**

Bend type

## **Fsc Application Data:**

Antennas, waveguides, and related equipment

#### Shelf Life:

N/a

## Unit Of Measure:

--

# Demilitarization:

Yes - demil/mli

# NSN 5985-01-313-3856

Waveguide Assembly - Page 2 of 2

Fiig: A073a0

