## NSN 5985-01-315-6411



Fixed Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-01-315-6411 **Application Design:** Transmission line **Body Material:** Steel, stainless **Body Style:** Err-090 **Body Surface Treatment:** Any acceptable **Overall Length:** Between 0.820 inches and 0.900 inches **Overall Diameter:** Between 0.260 inches and 0.300 inches **End Application:** Aircraft, eagle f-15 **Voltage Standing Wave Ratio:** 1.12 and 1.15 and 1.20 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Sma **Power Rating:** 2.0 watts average Rf Signal Attenuation In Decibels: 1.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+18.0 gigahertz **Attenuation Accuracy Reference Frequency:** 18.0 gigahertz **Attenuation Accuracy In Decibels:** -0.30/+0.30 **Connection Type Per Function:** Female input and male output **Mounting Method:** Connector

## **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz **Criticality Code Justification:**

Feat

## NSN 5985-01-315-6411

Fixed Attenuator - Page 2 of 2



Special	Features:
---------	-----------

Weapon system essental

**Specification Data:** 

14482-267582 manufacturers specification control

**Fsc Application Data:** 

Antennas, waveguides, and related equipment

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000