NSN 5985-01-316-6766

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-316-6766

Application Designs
Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
5.600 inches
Overall Height:
1.700 inches
Overall Width:
2.900 inches
Voltage Standing Wave Ratio:
1.50 and 1.60 and 1.90
Coaxial Connector Series Designation:
N
Power Rating:
1.0 watts average and 100.0 watts peak
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.6
Overall Attenuation Range In Decibels:
+0.0/+110.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
11
Attenuation Per Step In Decibels:
10.0 and 20.0 and 30.0 and 40.0 and 50.0 and 60.0 and 70.0 and 80.0 and 90.0 and 100.0 and 110.0
Mounting Facility Type And Quantity:
1 free standing base
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz
Overall Attenuation Accuracy In Decibels:
-4.40/+4.40
Adjustment Device Type And Quantity:
1 knob w/dial
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Terminal Type And Quantity:
1 connector, coaxial, female
Fsc Application Data:

Communication equipment

NSN 5985-01-316-6766

Variable Attenuator - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0