

View Online at <https://aerobasegroup.com/nsn/5985-01-317-6572>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b all flanges single connection facility

Thread Direction:

Right-hand all flanges single connection facility

Bend Angle In Deg:

90.0 second bend e-plane

End Application:

Training set, electronic warfare an/mst-t1v

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.118 inches all flanges and 1.126 inches all flanges

Flange Inside Height:

0.493 inches all flanges and 0.501 inches all flanges

Flange Outside Width:

1.860 inches all flanges and 1.890 inches all flanges

Flange Outside Height:

1.860 inches all flanges and 1.890 inches all flanges

Flange Inside Diameter:

1.610 inches all flanges and 1.640 inches all flanges

Flange Depth:

0.610 inches all flanges and 0.640 inches all flanges

Maximum Operating Pressure:

20.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

Thread Size:

0.164 inches all flanges single connection facility

Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

Flange Connecting Facility And Quantity:

4 threaded hole all flanges single connection facility

Flange Style:

Choke type all flanges

Waveguide Length:

Between 23.320 inches and 23.380 inches

Special Features:

Frequency range 7.05 to 10.0 ghz

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy all tubing segment and flange

Surface Treatment:

Primer all tubing segment and flange outside surfaces

Style Designator:

Offset bend type

Thread Series Designator:

Unc all flanges single connection facility

Fsc Application Data:

Radar equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A073a0