NSN 5985-01-317-6573

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-317-6573

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b all flanges single connection facility

Thread Direction:

Right-hand all flanges single connection facility

Bend Angle In Deg:

90.0 second bend e-plane

End Application:

Training set, electronic warfare an/mst-t1v

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.867 inches all flanges and 1.877 inches all flanges

Flange Inside Height:

0.867 inches all flanges and 0.877 inches all flanges

Flange Outside Diameter:

3.610 inches all flanges and 3.640 inches all flanges

Flange Depth:

0.922 inches all flanges and 0.953 inches all flanges

Maximum Operating Pressure:

20.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.995 inches and 2.005 inches

Thread Size:

0.190 inches all flanges single connection facility

Waveguide Inside Width:

Between 1.867 inches and 1.877 inches

Waveguide Inside Height:

Between 0.867 inches and 0.877 inches

Waveguide Outside Height:

Between 0.995 inches and 1.005 inches

Flange Connecting Facility And Quantity:

8 threaded hole all flanges single connection facility

Flange Style:

Choke type all flanges

Waveguide Length:

Between 20.370 inches and 20.430 inches

Flexibility:

Rigid single tubing segment

NSN 5985-01-317-6573

Waveguide Assembly - Page 2 of 2



Material:
Aluminum alloy all tubing segment and flange
Surface Treatment:
Primer all tubing segment and flange outside surfaces
Style Designator:
Offset bend type
Thread Series Designator:
Unf all flanges single connection facility
Fsc Application Data:
Radar equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A073a0