

View Online at <https://aerobasegroup.com/nsn/5985-01-317-6579>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:**

2b first flange single connection facility

**Thread Direction:**

Right-hand first flange single connection facility

**End Application:**

Training set, electronic warfare an/mst-t1v

**Tubing Wall Construction Style:**

Seamless single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

2.002 inches second flange

**Flange Inside Height:**

1.002 inches second flange

**Flange Outside Diameter:**

3.610 inches second flange and 3.640 inches second flange

**Flange Depth:**

0.922 inches first flange and 0.953 inches first flange

**Flange Connecting Hole Diameter:**

0.199 inches second flange single connection facility

**Voltage Standing Wave Ratio:**

1.08

**Maximum Operating Pressure:**

30.0 pounds per square inch gage

**Waveguide Outside Width:**

Between 1.995 inches and 2.005 inches

**Thread Size:**

0.190 inches first flange single connection facility

**Waveguide Inside Width:**

Between 1.867 inches and 1.877 inches

**Waveguide Inside Height:**

Between 0.867 inches and 0.877 inches

**Waveguide Outside Height:**

Between 0.995 inches and 1.005 inches

**Flange Connecting Facility And Quantity:**

8 unthreaded hole second flange single connection facility

**Flange Style:**

Cover type second flange

**Waveguide Length:**

Between 8.880 inches and 9.120 inches

**Flexibility:**

Flexible single tubing segment

**Material:**

Aluminum alloy all tubing segment and flange

**Style Designator:**

Straight type

**Thread Series Designator:**

Unf first flange single connection facility

**Specification Data:**

81755-654ve7190 manufacturers specification control

**Fsc Application Data:**

Radar equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A073a0