# NSN 5985-01-318-4455

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-318-4455

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

## **Thread Class:**

2a first flange all connection facilities

## **Thread Direction:**

Right-hand first flange all connection facilities

#### **End Application:**

Radio terminal set an/trc-170

#### Tubing Wall Construction Style:

Seamless second tubing segment

## **Tubing Twist Type:**

Twistable first tubing segment

#### **Tubing Twist Angle In Deg:**

90.0 first tubing segment

#### Flange Quantity:

3

#### Flange Inside Width:

1.867 inches first flange and 1.877 inches first flange

#### Flange Inside Height:

0.867 inches first flange and 0.877 inches first flange

## Flange Outside Diameter:

3.610 inches first flange and 3.640 inches first flange

## Flange Depth:

0.923 inches first flange and 0.953 inches first flange

## Voltage Standing Wave Ratio:

1.10

## Waveguide Outside Width:

2.000 inches

## Thread Size:

0.190 inches first flange all connection facilities

## Waveguide Inside Width:

1.872 inches

## Waveguide Inside Height:

0.872 inches

## Waveguide Outside Height:

1.000 inches

## Flange Connecting Facility And Quantity:

8 threaded hole first flange all connection facilities

#### Flange Style:

Choke type first flange

#### Flexibility:

Rigid second tubing segment

## NSN 5985-01-318-4455

Waveguide Assembly - Page 2 of 2



Material:

Copper alloy first tubing segment

**Precious Material And Location:** 

Internal surfaces silver

Precious Material:

Silver

Surface Treatment:

Copper alloy all tubing segment and flange inside surfaces or silver all tubing segment and flange inside surfaces

## **Thread Series Designator:**

Unf first flange all connection facilities

#### **Fsc Application Data:**

Antennas, waveguides, and related equip.

#### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

Yes - demil/mli

Fiig:

A073a0