## NSN 5985-01-318-4455

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-318-4455

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2a first flange all connection facilities

**Thread Direction:** 

Right-hand first flange all connection facilities

**End Application:** 

Radio terminal set an/trc-170

**Tubing Wall Construction Style:** 

Seamless second tubing segment

**Tubing Twist Type:** 

Twistable first tubing segment

**Tubing Twist Angle In Deg:** 

90.0 first tubing segment

Flange Quantity:

3

## Flange Inside Width:

1.867 inches first flange and 1.877 inches first flange

Flange Inside Height:

0.867 inches first flange and 0.877 inches first flange

Flange Outside Diameter:

3.610 inches first flange and 3.640 inches first flange

Flange Depth:

0.923 inches first flange and 0.953 inches first flange

**Voltage Standing Wave Ratio:** 

1.10

**Waveguide Outside Width:** 

2.000 inches

**Thread Size:** 

0.190 inches first flange all connection facilities

Waveguide Inside Width:

1.872 inches

**Waveguide Inside Height:** 

0.872 inches

**Waveguide Outside Height:** 

1.000 inches

Flange Connecting Facility And Quantity:

8 threaded hole first flange all connection facilities

Flange Style:

Choke type first flange

Flexibility:

Rigid second tubing segment

## **NSN 5985-01-318-4455** Waveguide Assembly - Page 2 of 2



Material:
Copper alloy first tubing segment
Precious Material And Location:
Internal surfaces silver
Precious Material:
Silver
Surface Treatment:
Copper alloy all tubing segment and flange inside surfaces or silver all tubing segment and flange inside surfaces
Thread Series Designator:
Unf first flange all connection facilities
Fsc Application Data:
Antennas, waveguides, and related equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A073a0