

View Online at <https://aerobasegroup.com/nsn/5985-01-318-4458>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

End Application:

Radio terminal set an/trc-170

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

1.867 inches first flange and 1.877 inches first flange

Flange Inside Height:

0.867 inches first flange and 0.877 inches first flange

Flange Outside Diameter:

3.610 inches first flange and 3.640 inches first flange

Flange Depth:

0.922 inches first flange and 0.953 inches first flange

Voltage Standing Wave Ratio:

1.15

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.995 inches and 2.005 inches

Thread Size:

0.190 inches first flange single connection facility

Waveguide Inside Width:

Between 1.867 inches and 1.877 inches

Waveguide Inside Height:

Between 0.867 inches and 0.877 inches

Waveguide Outside Height:

Between 0.995 inches and 1.005 inches

Flange Connecting Facility And Quantity:

8 threaded hole first flange single connection facility

Waveguide First Leg Length:

Between 2.190 inches and 2.310 inches

Flange Style:

Choke type first flange

Waveguide Second Leg Length:

Between 47.880 inches and 48.000 inches

Waveguide Third Leg Length:

Between 1.940 inches and 2.060 inches

Waveguide Fourth Leg Length:

Between 2.940 inches and 3.060 inches

Flexibility:

Rigid all tubing segment

Material:

Aluminum alloy 6061 all tubing segment and flange

Surface Treatment:

Chromate all tubing segment and flange all surfaces

Style Designator:

Three bend type

Thread Series Designator:

Unf first flange single connection facility

Fsc Application Data:

Communication equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0