

View Online at <https://aerobasegroup.com/nsn/5985-01-318-6663>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2a first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

End Application:

Radio terminal set an/trc-170

Tubing Wall Construction Style:

Seamless second tubing segment

Tubing Twist Type:

Twistable first tubing segment

Tubing Twist Angle In Deg:

90.0 first tubing segment

Flange Quantity:

3

Flange Inside Width:

1.867 inches first flange and 1.877 inches first flange

Flange Inside Height:

0.867 inches first flange and 0.877 inches first flange

Flange Outside Diameter:

3.610 inches first flange and 3.640 inches first flange

Flange Depth:

0.923 inches first flange and 0.953 inches first flange

Voltage Standing Wave Ratio:

1.08

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

2.000 inches

Thread Size:

0.190 inches first flange all connection facilities

Waveguide Inside Width:

1.872 inches

Waveguide Inside Height:

0.872 inches

Waveguide Outside Height:

1.000 inches

Flange Connecting Facility And Quantity:

8 threaded hole first flange all connection facilities

Flange Style:

Choke type first flange

Flexibility:

Rigid second tubing segment

Material:

Copper alloy all tubing segment

Precious Material And Location:

Internal surfaces silver

Precious Material:

Silver

Surface Treatment:

Copper alloy all tubing segment and flange inside surfaces or silver all tubing segment and flange inside surfaces

Thread Series Designator:

Unf first flange all connection facilities

Fsc Application Data:

Antennas, waveguides, and related equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0