

View Online at <https://aerobasegroup.com/nsn/5985-01-318-7870>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b all flanges all connection facilities

Thread Direction:

Right-hand all flanges all connection facilities

Bend Angle In Deg:

90.0 third bend h-plane

End Application:

Radio terminal set an/trc-170

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

1.867 inches all flanges and 1.877 inches all flanges

Flange Inside Height:

0.867 inches all flanges and 0.877 inches all flanges

Flange Outside Diameter:

3.610 inches all flanges and 3.640 inches all flanges

Flange Depth:

0.922 inches all flanges and 0.953 inches all flanges

Voltage Standing Wave Ratio:

1.12

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.995 inches and 2.005 inches

Thread Size:

0.190 inches all flanges all connection facilities

Waveguide Inside Width:

Between 1.867 inches and 1.877 inches

Waveguide Inside Height:

Between 0.867 inches and 0.877 inches

Waveguide Outside Height:

Between 0.995 inches and 1.005 inches

Flange Connecting Facility And Quantity:

8 threaded hole all flanges all connection facilities

Waveguide First Leg Length:

Between 2.190 inches and 2.310 inches

Waveguide Fifth Leg Length:

Between 2.190 inches and 2.310 inches

Flange Style:

Choke type all flanges

Waveguide Second Leg Length:

Between 3.690 inches and 3.810 inches

Waveguide Third Leg Length:

Between 38.890 inches and 39.010 inches

Waveguide Fourth Leg Length:

Between 8.030 inches and 8.150 inches

Flexibility:

Rigid all tubing segment

Material:

Aluminum alloy 6061 all tubing segment and flange

Surface Treatment:

Chromate all tubing segment and flange all surfaces

Style Designator:

Four bend type

Thread Series Designator:

Unf all flanges all connection facilities

Fsc Application Data:

Communication equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A073a0