NSN 5985-01-319-1702

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-319-1702

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2a first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

End Application:

Radio terminal set an/trc-170

Tubing Wall Construction Style:

Seamless third tubing segment

Flange Quantity:

2

Flange Inside Width:

1.867 inches first flange and 1.877 inches first flange

Flange Inside Height:

0.867 inches first flange and 0.877 inches first flange

Flange Outside Diameter:

3.610 inches first flange and 3.640 inches first flange

Flange Depth:

0.923 inches first flange and 0.953 inches first flange

Voltage Standing Wave Ratio:

1.15

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

2.000 inches

Thread Size:

0.190 inches first flange all connection facilities

Waveguide Inside Width:

1.872 inches

Waveguide Inside Height:

0.872 inches

Waveguide Outside Height:

1.000 inches

Flange Connecting Facility And Quantity:

8 threaded hole first flange all connection facilities

Flange Style:

Choke type first flange

Flexibility:

Rigid third tubing segment

Material:

Copper alloy all tubing segment

NSN 5985-01-319-1702 Waveguide Assembly - Page 2 of 2



Precious Material And Location:
Internal surfaces silver
Precious Material:
Silver
Surface Treatment:
Copper alloy all tubing segment and flange inside surfaces or silver all tubing segment and flange inside surfaces
Thread Series Designator:
Unf first flange all connection facilities
Fsc Application Data:
Antennas, waveguies, and related equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A073a0