

View Online at <https://aerobasegroup.com/nsn/5985-01-319-3055>

Cross Sectional Shape:

Internal, rectangular external, rectangular

End Application:

Test set, swept frequency measurement an/usm-482

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

1

Flange Inside Width:

0.705 inches single flange

Flange Inside Height:

0.394 inches single flange

Flange Outside Width:

1.298 inches single flange and 1.328 inches single flange

Flange Outside Height:

1.298 inches single flange and 1.328 inches single flange

Flange Depth:

0.298 inches single flange and 0.328 inches single flange

Flange Connecting Hole Diameter:

0.144 inches single flange all connection facilities

Voltage Standing Wave Ratio:

1.25

Insertion Loss In Decibels:

0.30

Coaxial Connector Series Designation:

N

Connector End Design:

Female

Adapter Length:

1.600 inches

Adapter Height:

Between 1.298 inches and 1.328 inches

Waveguide Outside Width:

Between 0.699 inches and 0.705 inches

Waveguide Inside Width:

Between 0.6195 inches and 0.6245 inches

Waveguide Inside Height:

Between 0.3085 inches and 0.3135 inches

Waveguide Outside Height:

Between 0.388 inches and 0.394 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole single flange all connection facilities

Flange Style:

Cover type single flange

Adapterheight:

2.500 inches

Adapterwidth:

Between 1.298 inches and 1.328 inches

Material:

Aluminum alloy single tubing segment and flange

Surface Treatment:

Enamel single tubing segment and flange outside surfaces

Style Designator:

Waveguide to coaxial

Fsc Application Data:

Microwave equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0