

View Online at <https://aerobasegroup.com/nsn/5985-01-319-3056>

Cross Sectional Shape:

Internal, rectangular external, rectangular

End Application:

Test set, swept frequency measurement an/usm-482

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

1

Flange Inside Width:

1.253 inches single flange

Flange Inside Height:

0.628 inches single flange

Flange Outside Width:

1.860 inches single flange and 1.890 inches single flange

Flange Outside Height:

1.860 inches single flange and 1.890 inches single flange

Flange Depth:

0.423 inches single flange and 0.453 inches single flange

Flange Connecting Hole Diameter:

0.169 inches single flange all connection facilities

Voltage Standing Wave Ratio:

1.25

Insertion Loss In Decibels:

0.30

Coaxial Connector Series Designation:

N

Connector End Design:

Male

Adapter Length:

1.650 inches

Adapter Height:

Between 1.860 inches and 1.890 inches

Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole single flange all connection facilities

Flange Style:

Cover type single flange

Adapterheight:

2.700 inches

Adapterwidth:

Between 1.860 inches and 1.890 inches

Material:

Aluminum alloy single tubing segment and flange

Surface Treatment:

Enamel single tubing segment and flange outside surfaces

Style Designator:

Waveguide to coaxial

Fsc Application Data:

Microwave equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0