NSN 5985-01-320-4418

Fixed Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Material:



View Online at https://aerobasegroup.com/nsn/5985-01-320-4418

Brass
Body Style:
Err-090
Overall Length:
3.400 inches
Overall Diameter:
0.910 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.15 and 1.20 and 1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
5.0 watts average and 1.0 kilowatts peak
Rf Signal Attenuation In Decibels:
50.0
Attenuation Accuracy In Decibels:
-1.25/+1.25
Temperature Sensitivity Attenuation In Decibels:
0.0004
0.0001
Connection Type Per Function:
Connection Type Per Function:
Connection Type Per Function: Female input and male output
Connection Type Per Function: Female input and male output Unpackaged Unit Weight:
Connection Type Per Function: Female input and male output Unpackaged Unit Weight: 0.130 kilograms
Connection Type Per Function: Female input and male output Unpackaged Unit Weight: 0.130 kilograms Mounting Method:
Connection Type Per Function: Female input and male output Unpackaged Unit Weight: 0.130 kilograms Mounting Method: Connector
Connection Type Per Function: Female input and male output Unpackaged Unit Weight: 0.130 kilograms Mounting Method: Connector Terminal Type And Quantity:
Connection Type Per Function: Female input and male output Unpackaged Unit Weight: 0.130 kilograms Mounting Method: Connector Terminal Type And Quantity: 2 connector
Connection Type Per Function: Female input and male output Unpackaged Unit Weight: 0.130 kilograms Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range:
Connection Type Per Function: Female input and male output Unpackaged Unit Weight: 0.130 kilograms Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz
Connection Type Per Function: Female input and male output Unpackaged Unit Weight: 0.130 kilograms Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz Precious Material And Location:
Connection Type Per Function: Female input and male output Unpackaged Unit Weight: 0.130 kilograms Mounting Method: Connector Terminal Type And Quantity: 2 connector Frequency Range: Between 0.000 hertz and 18.000 gigahertz Precious Material And Location: Contact surfaces gold

NSN 5985-01-320-4418

Fixed Attenuator - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000