NSN 5985-01-321-8313

Variable Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-321-8313

| Application Design: |
|---|
| Transmission line |
| Body Style: |
| Coaxial type |
| Overall Length: |
| 2.750 inches |
| Overall Diameter: |
| 1.000 inches |
| End Application: |
| Communications restoral system an/tsc-115 |
| Voltage Standing Wave Ratio: |
| 1.25 |
| Coaxial Connector Series Designation: |
| Tnc |
| Power Rating: |
| 10.0 watts average and 5.0 kilowatts peak |
| Overall Attenuation Range In Decibels: |
| +3.0/+40.0 |
| Attenuation Variation Method: |
| Stepped |
| Step Position Quantity: |
| 37 |
| Attenuation Per Step In Decibels: |
| 1.0 |
| Frequency Range: |
| Between 0.000 hertz and 2.000 gigahertz |
| Overall Attenuation Accuracy In Decibels: |
| -3.00/+10.00 |
| Adjustment Device Type And Quantity: |
| 1 electronic, voltage controlled |
| Impedance Rating In Ohms: |
| 50.0 input-output |
| Terminal Type And Quantity: |
| 1 connector, coaxial, female and 1 connector, coaxial, male |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A223a0 |
| |