

NSN 5985-01-321-8988 Fixed Attenuator - Page 1 of 2	AeroBase Group		
View Online at https://aerobasegroup.com/nsn/5985-01-321-8988			
Application Design:			
Transmission line			
Body Material:			
Steel, stainless			
Body Style:			
Rectangular, terminal/terminals on opposite surfaces			
Body Surface Treatment:			
Passivated			
Overall Length:			
Between 0.840 inches and 0.880 inches			
Operating Tempurature Range:			
-55.0/+125.0 degrees celsius			
End Application:			
5840-01-086-8272 receiver, exciter			
Voltage Standing Ways Dation			

Voltage Standing Wave Ratio:

1.25

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

Sma

Power Rating:

2.0 watts average and 100.0 watts peak

Rf Signal Attenuation In Decibels:

13.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+8.0 gigahertz

Attenuation Accuracy In Decibels:

-0.50/+0.50

Unpackaged Unit Weight:

0.200 ounces

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 8.000 gigahertz

Specification Data:

05869-729053-13 manufacturers specification control

Fsc Application Data:

Communication equipment

NSN 5985-01-321-8988

Fixed Attenuator - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000