

View Online at <https://aerobasegroup.com/nsn/5985-01-321-9498>

Application Design:

Transmission line

Body Material:

Steel, stainless

Body Style:

Err-090

Body Surface Treatment:

Passivated

Overall Length:

Between 0.840 inches and 0.880 inches

Overall Diameter:

0.312 inches

Operating Temperature Range:

-65.0/+125.0 degrees celsius

End Application:

5840-01-086-8272 receiver, exciter

Voltage Standing Wave Ratio:

1.07

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

Sma

Power Rating:

2.0 watts average and 100.0 watts peak

Rf Signal Attenuation In Decibels:

12.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+8.0 gigahertz

Attenuation Accuracy Reference Frequency:

8.0 gigahertz

Attenuation Accuracy In Decibels:

-0.50/+0.50

Connection Type Per Function:

Female input and male output

Unpackaged Unit Weight:

0.200 ounces

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 8.000 gigahertz

Specification Data:

05869-729053 manufacturers specification control

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000