## NSN 5985-01-322-4933

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-322-4933

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
3.000 inches
Overall Height:
2.500 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
2.688 inches
Voltage Standing Wave Ratio:
1.30
Coaxial Connector Series Designation:
Bnc
Power Rating:
1.0 watts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+15.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
2 unthreaded hole
Frequency Range:
Between 0.000 hertz and 100.000 megahertz
Overall Attenuation Accuracy In Decibels:
-0.30/+0.30
Adjustment Device Type And Quantity:
1 knob w/dial
Mounting Facility Pattern:
Two position in-line
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female
Fsc Application Data:
Communication equipment
Shelf Life:

N/a

## NSN 5985-01-322-4933

Variable Attenuator - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A223a0