

View Online at <https://aerobasegroup.com/nsn/5985-01-322-6618>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2a all flanges all connection facilities

Thread Direction:

Right-hand all flanges all connection facilities

Tubing Wall Construction Style:

Seamless second tubing segment

Tubing Twist Type:

Straight twist first tubing segment

Flange Quantity:

2

Flange Inside Width:

1.867 inches all flanges and 1.877 inches all flanges

Flange Inside Height:

0.867 inches all flanges and 0.877 inches all flanges

Flange Outside Diameter:

3.610 inches all flanges and 3.640 inches all flanges

Flange Depth:

0.932 inches all flanges and 0.953 inches all flanges

Voltage Standing Wave Ratio:

1.05

Waveguide Outside Width:

Between 1.995 inches and 2.005 inches

Thread Size:

0.190 inches all flanges all connection facilities

Waveguide Inside Width:

Between 1.867 inches and 1.877 inches

Waveguide Inside Height:

Between 0.867 inches and 0.877 inches

Waveguide Outside Height:

Between 0.995 inches and 1.005 inches

Flange Connecting Facility And Quantity:

8 threaded hole all flanges all connection facilities

Flange Style:

Choke type all flanges

Waveguide Length:

6.385 inches

Flexibility:

Rigid second tubing segment

Material:

Aluminum alloy all tubing segment and flange

Style Designator:

Straight type

Thread Series Designator:

Unf all flanges all connection facilities

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0