NSN 5985-01-323-4931

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-323-4931 **Application Design:** Printed circuit board **Body Style:** Irregular **Overall Length:** 2.130 inches Center To Center Distance Between Mounting Facilities Parallel To Length: Between 1.490 inches and 1.510 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** Between 1.120 inches and 1.140 inches **Overall Height:** 1.000 inches **Overall Width:** 1.500 inches **Attenuation Variation Method:** Stepped **Step Position Quantity: Mounting Facility Type And Quantity:** 2 threaded hole Frequency Range: Between 360.000 hertz and 440.000 hertz **Mounting Thread Quantity:** 40 per inch **Mounting Facility Pattern:** Two position diagonal **Criticality Code Justification: Mounting Facility Screw Thread Diameter:** 0.112 inches **Special Features:** This device requires special handling and processing to prevent damage from electrostatic discharge transients **Test Data Document:** 81349-mil-std-202 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 5 tab, solder lug Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5985-01-323-4931

Variable Attenuator - Page 2 of 2



Fiig:

A223a0