## NSN 5985-01-324-5900

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-324-5900
Application Design:
Transmission line
Body Material:
Metal
Body Style:
Rectangular, terminal/terminals on opposite surfaces
Body Surface Treatment:
Any acceptable
Overall Length:
0.870 inches
Overall Height:
0.317 inches
Overall Width:
0.317 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.15
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average and 500.0 watts peak
Rf Signal Attenuation In Decibels:
3.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+18.0 gigahertz
Attenuation Accuracy In Decibels:
-0.30/+0.30
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz
Test Data Document:
81349-mil-a-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

81349-mil-a-3933/25 government specification

**Specification Data:** 

## NSN 5985-01-324-5900

Fixed Attenuator - Page 2 of 2



	Fsc	App	lication	Data:
--	-----	-----	----------	-------

Communication equipment

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A20000