NSN 5985-01-326-7689

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-326-7689
Application Design:
Transmission line
Body Material:
Metal
Body Style:
Err-090
Overall Length:
0.870 inches
Overall Diameter:
Between 0.260 inches and 0.300 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.15
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average and 500.0 watts peak
Rf Signal Attenuation In Decibels:
5.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+2.0 gigahertz
Attenuation Accuracy In Decibels:
-0.30/+0.30
Unpackaged Unit Weight:
0.450 ounces
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 2.000 gigahertz
Test Data Document:
81349-mil-a-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-a-3933/25 government specification
Fsc Application Data:

Microwave equipment

NSN 5985-01-326-7689

Fixed Attenuator - Page 2 of 2



Shelf L	ife:
---------	------

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000

Mil-std (military Standard):

Mil-a-3933 spec.