

View Online at <https://aerobasegroup.com/nsn/5985-01-328-1418>

**Application Design:**

Transmission line

**Voltage Standing Wave Ratio:**

1.20

**Power Rating:**

1.0 watts average

**Overall Attenuation Range In Decibels:**

+0.0/+22.1

**Attenuation Accuracy Reference Frequency:**

500.0 megahertz

**Attenuation Variation Method:**

Stepped

**Step Position Quantity:**

10

**Attenuation Per Step In Decibels:**

0.1 and 0.2 and 0.3 and 0.5 and 1.0 and 2.0 and 3.0 and 5.0 and 10.0 and 22.1

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Frequency Range:**

Between 0.000 hertz and 1000.000 megahertz

**Overall Attenuation Accuracy In Decibels:**

-0.50/+0.50

**Segment Attenuation Range In Decibels:**

+0.00/+0.10 and +0.10/+0.20 and +0.20/+0.30 and +0.30/+0.50 and +0.50/+1.00 and +1.00/+2.00 and +2.00/+3.00 and +3.00/+5.00 and +5.00/+10.00 and +10.00/+22.10

**Segment Attenuation Accuracy In Decibels:**

-0.50/+0.50

**Adjustment Device Type And Quantity:**

9 toggle

**Impedance Rating In Ohms:**

50.0 input-output

**Fsc Application Data:**

Antennas, waveguides, and related equip

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A223a0