

View Online at <https://aerobasegroup.com/nsn/5985-01-328-1418>

Application Design:

Transmission line

Voltage Standing Wave Ratio:

1.20

Power Rating:

1.0 watts average

Overall Attenuation Range In Decibels:

+0.0/+22.1

Attenuation Accuracy Reference Frequency:

500.0 megahertz

Attenuation Variation Method:

Stepped

Step Position Quantity:

10

Attenuation Per Step In Decibels:

0.1 and 0.2 and 0.3 and 0.5 and 1.0 and 2.0 and 3.0 and 5.0 and 10.0 and 22.1

Mounting Facility Type And Quantity:

4 unthreaded hole

Frequency Range:

Between 0.000 hertz and 1000.000 megahertz

Overall Attenuation Accuracy In Decibels:

-0.50/+0.50

Segment Attenuation Range In Decibels:

+0.00/+0.10 and +0.10/+0.20 and +0.20/+0.30 and +0.30/+0.50 and +0.50/+1.00 and +1.00/+2.00 and +2.00/+3.00 and +3.00/+5.00 and +5.00/+10.00 and +10.00/+22.10

Segment Attenuation Accuracy In Decibels:

-0.50/+0.50

Adjustment Device Type And Quantity:

9 toggle

Impedance Rating In Ohms:

50.0 input-output

Fsc Application Data:

Antennas, waveguides, and related equip

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0