

View Online at <https://aerobasegroup.com/nsn/5985-01-329-7762>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b all flanges all connection facilities

Thread Direction:

Right-hand all flanges all connection facilities

Bend Angle In Deg:

90.0 single bend h-plane

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

0.896 inches all flanges and 0.904 inches all flanges

Flange Inside Height:

0.396 inches all flanges and 0.404 inches all flanges

Flange Outside Width:

1.610 inches all flanges and 1.640 inches all flanges

Flange Outside Height:

1.610 inches all flanges and 1.640 inches all flanges

Flange Inside Diameter:

1.406 inches all flanges and 1.437 inches all flanges

Flange Depth:

0.423 inches all flanges and 0.453 inches all flanges

Voltage Standing Wave Ratio:

1.05

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Thread Size:

0.164 inches all flanges all connection facilities

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Waveguide Longer Offset Distance:

1.750 inches

Flange Connecting Facility And Quantity:

4 threaded hole all flanges all connection facilities

Flange Style:

Choke type all flanges

Waveguide Offset Distance:

1.125 inches

Special Features:

Frequency range 8.2 to 12.4 ghz

Flexibility:

Rigid all tubing segment

Material:

Aluminum alloy all tubing segment and flange

Surface Treatment:

Chromate all tubing segment and flange all surfaces

Style Designator:

Corner type

Thread Series Designator:

Unc all flanges all connection facilities

Fsc Application Data:

Radar equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A073a0