NSN 5985-01-330-7786

Fixed Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-330-7786

Application Design:
Transmission line
Body Style:
Rectangular terminal/terminals on three surfaces
Overall Length:
Between 0.865 inches and 0.875 inches
Overall Height:
0.055 inches
Overall Width:
Between 0.490 inches and 0.500 inches
Voltage Standing Wave Ratio:
1.30
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Power Rating:
1.0 watts average and 100.0 watts peak
Rf Signal Attenuation In Decibels:
2.0
2.0 Voltage Standing Wave Ratio Frequency Range:

Voltage Standing Wave Ratio Frequency Range:
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz Attenuation Accuracy In Decibels:
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz Attenuation Accuracy In Decibels: -0.20/+0.20
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz Attenuation Accuracy In Decibels: -0.20/+0.20 Terminal Type And Quantity:
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz Attenuation Accuracy In Decibels: -0.20/+0.20 Terminal Type And Quantity: 3 tab, solder lug
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz Attenuation Accuracy In Decibels: -0.20/+0.20 Terminal Type And Quantity: 3 tab, solder lug Frequency Range:
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz Attenuation Accuracy In Decibels: -0.20/+0.20 Terminal Type And Quantity: 3 tab, solder lug Frequency Range: Between 0.000 hertz and 4.000 gigahertz
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz Attenuation Accuracy In Decibels: -0.20/+0.20 Terminal Type And Quantity: 3 tab, solder lug Frequency Range: Between 0.000 hertz and 4.000 gigahertz Precious Material And Location:
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz Attenuation Accuracy In Decibels: -0.20/+0.20 Terminal Type And Quantity: 3 tab, solder lug Frequency Range: Between 0.000 hertz and 4.000 gigahertz Precious Material And Location: Tab surface gold
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz Attenuation Accuracy In Decibels: -0.20/+0.20 Terminal Type And Quantity: 3 tab, solder lug Frequency Range: Between 0.000 hertz and 4.000 gigahertz Precious Material And Location: Tab surface gold Precious Material:
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz Attenuation Accuracy In Decibels: -0.20/+0.20 Terminal Type And Quantity: 3 tab, solder lug Frequency Range: Between 0.000 hertz and 4.000 gigahertz Precious Material And Location: Tab surface gold Precious Material: Gold
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz Attenuation Accuracy In Decibels: -0.20/+0.20 Terminal Type And Quantity: 3 tab, solder lug Frequency Range: Between 0.000 hertz and 4.000 gigahertz Precious Material And Location: Tab surface gold Precious Material: Gold Shelf Life:
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz Attenuation Accuracy In Decibels: -0.20/+0.20 Terminal Type And Quantity: 3 tab, solder lug Frequency Range: Between 0.000 hertz and 4.000 gigahertz Precious Material And Location: Tab surface gold Precious Material: Gold Shelf Life: N/a
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz Attenuation Accuracy In Decibels: -0.20/+0.20 Terminal Type And Quantity: 3 tab, solder lug Frequency Range: Between 0.000 hertz and 4.000 gigahertz Precious Material And Location: Tab surface gold Precious Material: Gold Shelf Life: N/a

Yes - demil/mli

Fiig:

A20000