NSN 5985-01-330-9274

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-330-9274
Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Err-090
Body Surface Treatment:
Any acceptable
Overall Length:
1.020 inches
Overall Diameter:
0.312 inches
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.07
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
0.5 watts average and 2.0 watts peak
Rf Signal Attenuation In Decibels:
15.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+8.0 gigahertz
Attenuation Accuracy Reference Frequency:
8.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Connection Type Per Function:
Female input and male output
Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 8.000 gigahertz

Fsc Application Data:

Antennas, waveguides, and related equipment

NSN 5985-01-330-9274

Fixed Attenuator - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000