NSN 5985-01-330-9277

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-330-9277

Application Design:
Transmission line
Body Material:
Aluminum
Body Style:
Err-090
Body Surface Treatment:
Any acceptable
Overall Length:
4.090 inches
Overall Diameter:
1.640 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.20 and 1.30
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N and wpm
Power Rating:
20.0 watts average and 5.0 kilowatts peak
Rf Signal Attenuation In Decibels:
30.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+8.0 gigahertz
Attenuation Accuracy Reference Frequency:
4.0 gigahertz
Attenuation Accuracy In Decibels:
-0.40/+0.40
Connection Type Per Function:
Male input and female output
Unpackaged Unit Weight:
10.000 ounces
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Potwoon 0,000 bortz and 8,000 signbortz

Between 0.000 hertz and 8.000 gigahertz

NSN 5985-01-330-9277

Fixed Attenuator - Page 2 of 2



Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A20000