NSN 5985-01-331-0959

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-331-0959

Application Design:

Transmission line

Body Style:

Err-090

Overall Length:

0.870 inches

Overall Diameter:

Between 0.260 inches and 0.300 inches

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Voltage Standing Wave Ratio:

1.10 and 1.15 and 1.20 and 1.25

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

Sma

Power Rating:

2.0 watts average and 500.0 watts peak

Rf Signal Attenuation In Decibels:

12.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+2.0 gigahertz and +2.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz

Attenuation Accuracy In Decibels:

-0.40/+0.40

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 12.400 gigahertz

Test Data Document:

81349-mil-a-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-a-3933/25 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5985-01-331-0959

Fixed Attenuator - Page 2 of 2

Fiig: A20000

