NSN 5985-01-332-4595

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-332-4595
Application Design:
Transmission line
Body Material:
Copper alloy
Body Style:
Rectangular, terminal/terminals on one surface
Body Surface Treatment:
Tin plated
Overall Length:
Between 0.480 inches and 0.500 inches
Overall Height:
Between 0.377 inches and 0.457 inches
Overall Width:
Between 0.210 inches and 0.230 inches
Body Height:
Between 0.237 inches and 0.257 inches
Operating Tempurature Range:
-54.0/+100.0 degrees celsius
Voltage Standing Wave Ratio:
1.30
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Power Rating:
0.5 watts average
Rf Signal Attenuation In Decibels:
9.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+0.5 gigahertz and +0.5/+1.0 gigahertz and +1.0/+1.5 gigahertz
Center To Center Distance Between First And Second Terminals:
Between 0.090 inches and 0.110 inches
Center To Center Distance Between Second And Third Terminals:
Between 0.090 inches and 0.110 inches
Center To Center Distance Between Third And Fourth Terminals:
Between 0.090 inches and 0.110 inches
Attenuation Accuracy In Decibels:
-0.03/+0.03
Connection Type Per Function:
Male input and male output
Mounting Method:

Plug-in

NSN 5985-01-332-4595

Fixed Attenuator - Page 2 of 2



Terminal Type A	and Quantity	/:
-----------------	--------------	-----------

8 pin

Frequency Range:

Between 0.000 hertz and 1.500 gigahertz

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A20000