NSN 5985-01-332-5737

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-332-5737
Application Design:
Transmission line
Body Material:
Any acceptable
Body Style:
Err-090
Body Surface Treatment:
Any acceptable
Overall Length:
1.930 inches
Overall Diameter:
0.560 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Tnc
Power Rating:
4.0 watts average and 200.0 watts peak
Rf Signal Attenuation In Decibels:
4.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.5 gigahertz
Attenuation Accuracy In Decibels:
-0.40/+0.40
Connection Type Per Function:
Female input and male output
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 4.500 gigahertz
Test Data Document:
81349-mil-a-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

NSN 5985-01-332-5737

Fixed Attenuator - Page 2 of 2



Fsc Ap	plicatio	n Data:
--------	----------	---------

Communication equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000

Mil-std (military Standard):

Mil-a-3933 spec.