NSN 5985-01-332-6644

Fixed Attenuator - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5985-01-332-6644

Application Design:
Transmission line
Body Material:
Metal
Body Style:
Err-090
Overall Length:
Between 1.880 inches and 1.920 inches
Overall Diameter:
0.910 inches
Operating Tempurature Range:
-50.0/+85.0 degrees celsius
Voltage Standing Wave Ratio:
1.15 and 1.20 and 1.25 and 1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Wpm
Power Rating:
2.0 watts average and 500.0 watts peak
Rf Signal Attenuation In Decibels:
10.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz and +12.4/+18.0 gigahertz
Connection Type Per Function:
Female output and male input
Unpackaged Unit Weight:
5.000 ounces
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz
Special Features:
W/wpc-7 male connector
Fsc Application Data:
Antennas, waveguides, and related equip.
Shelf Life:

NSN 5985-01-332-6644

Fixed Attenuator - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000