

View Online at <https://aerobasegroup.com/nsn/5985-01-332-8793>

Application Design:

Printed circuit board

Body Style:

Irregular

Overall Length:

1.400 inches

Overall Height:

0.645 inches

Overall Width:

0.810 inches

End Application:

An/apm-424 test kit, transponder set

Voltage Standing Wave Ratio:

1.50

Insertion Loss At Minimum Attenuation In Maximum Decibels:

4.0

Overall Attenuation Range In Decibels:

+4.0/+24.0

Attenuation Variation Method:

Stepped

Step Position Quantity:

4

Attenuation Per Step In Decibels:

2.0 and 6.0 and 12.0

Frequency Range:

Between 900.000 megahertz and 1200.000 megahertz

Overall Attenuation Accuracy In Decibels:

-0.50/+1.00

Segment Attenuation Range In Decibels:

+4.00/+6.00 and +6.00/+12.00 and +12.00/+24.00

Adjustment Device Type And Quantity:

1 electronic, voltage controlled

Criticality Code Justification:

Feat

Impedance Rating In Ohms:

50.0 input-output

Special Features:

Weapon system essential

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Terminal Type And Quantity:

9 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A223a0