

View Online at <https://aerobasegroup.com/nsn/5985-01-332-8793>

**Application Design:**

Printed circuit board

**Body Style:**

Irregular

**Overall Length:**

1.400 inches

**Overall Height:**

0.645 inches

**Overall Width:**

0.810 inches

**End Application:**

An/apm-424 test kit, transponder set

**Voltage Standing Wave Ratio:**

1.50

**Insertion Loss At Minimum Attenuation In Maximum Decibels:**

4.0

**Overall Attenuation Range In Decibels:**

+4.0/+24.0

**Attenuation Variation Method:**

Stepped

**Step Position Quantity:**

4

**Attenuation Per Step In Decibels:**

2.0 and 6.0 and 12.0

**Frequency Range:**

Between 900.000 megahertz and 1200.000 megahertz

**Overall Attenuation Accuracy In Decibels:**

-0.50/+1.00

**Segment Attenuation Range In Decibels:**

+4.00/+6.00 and +6.00/+12.00 and +12.00/+24.00

**Adjustment Device Type And Quantity:**

1 electronic, voltage controlled

**Criticality Code Justification:**

Feat

**Impedance Rating In Ohms:**

50.0 input-output

**Special Features:**

Weapon system essential

**Precious Material And Location:**

Terminals gold

**Precious Material:**

Gold

**Terminal Type And Quantity:**

9 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A223a0