NSN 5985-01-333-0911

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-333-0911

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b second flange all connection facilities

Thread Direction:

Right-hand second flange all connection facilities

Tubing Wall Construction Style:

Corrugated single tubing segment

Tubing Twist Type:

Twistable single tubing segment

Tubing Twist Angle In Deg:

90.0 single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.703 inches first flange and 0.707 inches first flange

Flange Inside Height:

0.392 inches first flange and 0.396 inches first flange

Flange Outside Width:

1.298 inches first flange and 1.328 inches first flange

Flange Outside Height:

1.298 inches first flange and 1.328 inches first flange

Flange Depth:

0.360 inches second flange and 0.390 inches second flange

Flange Connecting Hole Diameter:

0.142 inches first flange all connection facilities and 0.146 inches first flange all connection facilities

Voltage Standing Wave Ratio:

1.12

Insertion Loss In Decibels:

0.10

Maximum Operating Pressure:

35.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.699 inches and 0.705 inches

Thread Size:

0.138 inches second flange all connection facilities

Waveguide Inside Width:

Between 0.6195 inches and 0.6245 inches

Waveguide Inside Height:

Between 0.3085 inches and 0.3135 inches

Waveguide Outside Height:

Between 0.388 inches and 0.394 inches

NSN 5985-01-333-0911 Waveguide Assembly - Page 2 of 2



Naveguide Longer Offset Distance:
7.550 inches
Flange Connecting Facility And Quantity:
4 unthreaded hole first flange all connection facilities
Flange Style:
Cover type first flange
Naveguide Offset Distance:
1.190 inches
Flexibility:
Flexible single tubing segment
Material:
Aluminum alloy all tubing segment and flange
Surface Treatment:
Paint single tubing segment and flange outside surfaces
Style Designator:
Bend type
Supplementary Features:
Frequency 12.79 to 15.21 ghz
Thread Series Designator:
Unc second flange all connection facilities
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A073a0