

View Online at <https://aerobasegroup.com/nsn/5985-01-333-1323>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Seamless second tubing segment

Tubing Twist Type:

Twistable third tubing segment

Tubing Twist Angle In Deg:

180.0 third tubing segment

Flange Quantity:

2

Flange Inside Width:

1.368 inches first flange and 1.376 inches first flange

Flange Inside Height:

0.618 inches first flange and 0.626 inches first flange

Flange Outside Diameter:

3.110 inches first flange and 3.140 inches first flange

Flange Depth:

0.735 inches first flange and 0.765 inches first flange

Voltage Standing Wave Ratio:

1.12

Insertion Loss In Decibels:

0.10

Maximum Operating Pressure:

45.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.496 inches and 1.504 inches

Thread Size:

0.190 inches first flange all connection facilities

Waveguide Inside Width:

Between 1.368 inches and 1.376 inches

Waveguide Inside Height:

Between 0.618 inches and 0.626 inches

Waveguide Outside Height:

Between 0.746 inches and 0.754 inches

Flange Connecting Facility And Quantity:

6 threaded hole first flange all connection facilities

Waveguide First Leg Length:

2.380 inches

Waveguide Fifth Leg Length:

1.940 inches

Flange Style:

Choke type first flange

Waveguide Second Leg Length:

3.980 inches

Waveguide Third Leg Length:

6.020 inches

Waveguide Fourth Leg Length:

6.190 inches

Flexibility:

Rigid fifth tubing segment

Material:

Aluminum all tubing segment and flange

Surface Treatment:

Paint all tubing segment and flange outside surfaces

Style Designator:

Four bend type

Supplementary Features:

Frequency 6.89 to 8.45 ghz

Thread Series Designator:

Unf first flange all connection facilities

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A073a0