

View Online at <https://aerobasegroup.com/nsn/5985-01-333-1328>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.502 inches second flange and 1.508 inches second flange

Flange Inside Height:

0.752 inches second flange and 0.758 inches second flange

Flange Outside Diameter:

3.110 inches second flange and 3.140 inches second flange

Flange Depth:

0.735 inches first flange and 0.765 inches first flange

Flange Connecting Hole Diameter:

0.195 inches second flange all connection facilities and 0.203 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.12

Insertion Loss In Decibels:

0.10

Maximum Operating Pressure:

45.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.496 inches and 1.504 inches

Thread Size:

0.190 inches first flange all connection facilities

Waveguide Inside Width:

Between 1.368 inches and 1.376 inches

Waveguide Inside Height:

Between 0.618 inches and 0.626 inches

Waveguide Outside Height:

Between 0.746 inches and 0.754 inches

Waveguide Longer Offset Distance:

1.500 inches

Flange Connecting Facility And Quantity:

6 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Offset Distance:

3.000 inches

Flexibility:

Rigid single tubing segment

Material:

Aluminum all tubing segment and flange

Surface Treatment:

Paint all tubing segment and flange outside surfaces

Style Designator:

Bend type

Supplementary Features:

Frequency 6.89 to 8.45 ghz

Thread Series Designator:

Unf first flange all connection facilities

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A073a0