NSN 5985-01-333-1331

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-333-1331

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Seamless second tubing segment

Tubing Twist Type:

Twistable first tubing segment

Tubing Twist Angle In Deg:

90.0 first tubing segment

Flange Quantity:

2

Flange Inside Width:

1.250 inches all flanges and 1.256 inches all flanges

Flange Inside Height:

0.617 inches all flanges and 0.623 inches all flanges

Flange Outside Width:

1.860 inches all flanges and 1.890 inches all flanges

Flange Outside Height:

1.860 inches all flanges and 1.890 inches all flanges

Flange Depth:

0.415 inches all flanges and 0.445 inches all flanges

Flange Connecting Hole Diameter:

0.164 inches all flanges all connection facilities and 0.174 inches all flanges all connection facilities

Voltage Standing Wave Ratio:

1.12

Insertion Loss In Decibels:

0.10

Maximum Operating Pressure:

40.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges all connection facilities

Waveguide First Leg Length:

3.500 inches

Flange Style:

Cover type all flanges

NSN 5985-01-333-1331 Waveguide Assembly - Page 2 of 2



Waveguide Second Leg Length:
2.690 inches
Waveguide Third Leg Length:
3.125 inches
Waveguide Fourth Leg Length:
2.500 inches
Flexibility:
Rigid second tubing segment
Material:
Aluminum alloy all tubing segment and flange
Surface Treatment:
Paint all tubing segment and flange outside surfaces
Style Designator:
Three bend type
Supplementary Features:
Frequency 8.49 to 9.61 ghz
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A073a0