## NSN 5985-01-333-1495

Variable Attenuator - Page 1 of 2

Between 4.165 inches and 4.185 inches

Between 0.990 inches and 1.010 inches

Between 1.365 inches and 1.385 inches

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:

**Overall Height:** 

**Overall Width:** 



View Online at https://aerobasegroup.com/nsn/5985-01-333-1495

Detween 1.303 inches and 1.303 inches
Voltage Standing Wave Ratio:
1.40
Coaxial Connector Series Designation:
Sma
Power Rating:
0.5 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0/+63.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
6
Attenuation Per Step In Decibels:
1.0 and 2.0 and 4.0 and 8.0 and 16.0
Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:
Between 0.000 hertz and 1.000 gigahertz
Overall Attenuation Accuracy In Decibels:
-1.00/+1.00
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 electronic, programmable
Mounting Facility Screw Thread Diameter:
0.164 inches
Terminal Type And Quantity:
2 connector, coaxial, female and 7 pin
Shelf Life:
N/a

## NSN 5985-01-333-1495

Variable Attenuator - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A223a0