NSN 5985-01-333-2213

Waveguide Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-333-2213

| Cross Sectional Shape: |
|--|
| Internal, rectangular external, rectangular |
| End Application: |
| Transmitting set, radar an/tpt-t (v) |
| Flange Quantity: |
| 2 |
| Voltage Standing Wave Ratio: |
| 1.12 |
| Insertion Loss In Decibels: |
| 0.10 |
| Waveguide Outside Width: |
| 3.000 inches |
| Waveguide Inside Width: |
| 2.840 inches |
| Waveguide Inside Height: |
| 1.340 inches |
| Waveguide Outside Height: |
| 1.500 inches |
| Waveguide Longer Offset Distance: |
| Between 9.970 inches and 10.030 inches |
| Waveguide Offset Distance: |
| Between 5.380 inches and 5.440 inches |
| Special Features: |
| Frequency range 2.85 to 3.05 ghz |
| Flexibility: |
| Flexible all tubing segment |
| Material: |
| Aluminum all tubing segment and flange |
| Surface Treatment: |
| Paint all tubing segment and flange outside surfaces |
| Style Designator: |
| Bend type |
| Fsc Application Data: |
| Radar equipment |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| File: |

A073a0