NSN 5985-01-333-4300

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-333-4300

Cross Sectional Shape:
Internal, rectangular external, rectangular
End Application:
Transmitting set, radar an/tpt-t (v)
Flange Quantity:
2
Voltage Standing Wave Ratio:
1.12
Insertion Loss In Decibels:
0.10
Maximum Operating Pressure:
30.0 pounds per square inch gage
Waveguide Outside Width:
3.000 inches
Waveguide Inside Width:
2.840 inches
Waveguide Inside Height:
1.340 inches
Waveguide Outside Height:
1.500 inches
Waveguide Longer Offset Distance:
Between 16.680 inches and 16.740 inches
Waveguide Offset Distance:
Between 12.350 inches and 12.410 inches
Special Features:
Frequency range 2.85 ghz to 3.05 ghz
Flexibility:
Rigid fifth tubing segment
Material:
Aluminum all tubing segment and flange
Surface Treatment:
Paint all tubing segment and flange outside surfaces
Style Designator:
Bend type
Fsc Application Data:
Radar equipment
Shelf Life:
N/a
Unit Of Measure:

No

NSN 5985-01-333-4300

Waveguide Assembly - Page 2 of 2



Fiig:

A073a0