

View Online at <https://aerobasegroup.com/nsn/5985-01-333-6547>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b second flange all connection facilities

Thread Direction:

Right-hand second flange all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.250 inches first flange and 1.256 inches first flange

Flange Inside Height:

0.615 inches first flange and 0.625 inches first flange

Flange Outside Width:

1.860 inches second flange and 1.890 inches second flange

Flange Outside Height:

1.860 inches second flange and 1.890 inches second flange

Flange Depth:

0.610 inches second flange and 0.640 inches second flange

Flange Connecting Hole Diameter:

0.166 inches first flange all connection facilities and 0.172 inches first flange all connection facilities

Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

Thread Size:

0.164 inches second flange all connection facilities

Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

Waveguide Longer Offset Distance:

2.750 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole first flange all connection facilities

Flange Style:

Cover type first flange

Waveguide Offset Distance:

2.750 inches

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy single tubing segment and flange

Surface Treatment:

Chromate single tubing segment and flange outside surfaces and chromate zinc single tubing segment and flange outside surfaces and paint single tubing segment and flange outside surfaces

Style Designator:

Bend type

Thread Series Designator:

Unc second flange all connection facilities

Fsc Application Data:

Antennas, waveguides, and related equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0