NSN 5985-01-334-1109

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-334-1109

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b all flanges all connection facilities

Thread Direction:

Right-hand all flanges all connection facilities

Tubing Wall Construction Style:

Seamless third tubing segment

Tubing Twist Type:

Twistable first tubing segment

Tubing Twist Angle In Deg:

90.0 first tubing segment

Flange Quantity:

2

Flange Inside Width:

0.896 inches all flanges and 0.904 inches all flanges

Flange Inside Height:

0.396 inches all flanges and 0.404 inches all flanges

Flange Outside Width:

1.610 inches all flanges and 1.640 inches all flanges

Flange Outside Height:

1.610 inches all flanges and 1.640 inches all flanges

Flange Depth:

0.423 inches all flanges and 0.453 inches all flanges

Voltage Standing Wave Ratio:

1.15

Insertion Loss In Decibels:

0.13

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Thread Size:

0.164 inches all flanges all connection facilities

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Flange Connecting Facility And Quantity:

4 threaded hole all flanges all connection facilities

Waveguide First Leg Length:

2.870 inches

NSN 5985-01-334-1109

Waveguide Assembly - Page 2 of 2



| Waveguide Fifth Leg Length: |
|---|
| 3.250 inches |
| Flange Style: |
| Choke type all flanges |
| Waveguide Second Leg Length: |
| 1.730 inches |
| Waveguide Third Leg Length: |
| 5.320 inches |
| Waveguide Fourth Leg Length: |
| 1.150 inches |
| Special Features: |
| Flanges have resonance suppressor and captured screws included with each flange |
| Flexibility: |
| Rigid third tubing segment |
| Material: |
| Aluminum alloy all tubing segment and flange |
| Precious Material And Location: |
| Internal surfaces silver |
| Precious Material: |
| Silver |
| Surface Treatment: |
| Silver all tubing segment inside surfaces |
| Style Designator: |
| Four bend type |
| Thread Series Designator: |
| Unc all flanges all connection facilities |
| Fsc Application Data: |
| Antennas, waveguides, and related equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A073a0 |
| |
| |
| |