NSN 5985-01-334-1110

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-334-1110

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b all flanges all connection facilities

Thread Direction:

Right-hand all flanges all connection facilities

Tubing Wall Construction Style:

Seamless third tubing segment

Tubing Twist Type:

Twistable second tubing segment

Tubing Twist Angle In Deg:

90.0 second tubing segment

Flange Quantity:

2

Flange Inside Width:

0.896 inches all flanges and 0.904 inches all flanges

Flange Inside Height:

0.396 inches all flanges and 0.404 inches all flanges

Flange Outside Width:

1.610 inches all flanges and 1.640 inches all flanges

Flange Outside Height:

1.610 inches all flanges and 1.640 inches all flanges

Flange Depth:

0.423 inches all flanges and 0.453 inches all flanges

Voltage Standing Wave Ratio:

1.35

Insertion Loss In Decibels:

0.15

Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

Thread Size:

0.164 inches all flanges all connection facilities

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

Flange Connecting Facility And Quantity:

4 threaded hole all flanges all connection facilities

Waveguide First Leg Length:

3.240 inches

NSN 5985-01-334-1110

Waveguide Assembly - Page 2 of 2



Flange Style: Choke type all flanges Waveguide Second Leg Length: 7.970 inches Waveguide Third Leg Length: 2.180 inches Waveguide Fourth Leg Length: 1.700 inches **Special Features:** Flanges have resonance suppressor and captured screws included with each flange Flexibility: Rigid third tubing segment Material: Aluminum alloy all tubing segment and flange **Precious Material And Location:** Internal surfaces silver **Precious Material:** Silver Surface Treatment: Silver all tubing segment inside surfaces Style Designator: Three bend type **Thread Series Designator:** Unc all flanges all connection facilities Fsc Application Data: Antennas, waveguides, and related equip. Shelf Life: N/a Unit Of Measure: --**Demilitarization:** Yes - demil/mli Fiig: A073a0