NSN 5985-01-334-6741

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-334-6741

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b second flange all connection facilities

Thread Direction:

Right-hand second flange all connection facilities

Tubing Wall Construction Style:

Corrugated single tubing segment

Tubing Twist Type:

Twistable single tubing segment

Tubing Twist Angle In Deg:

90.0 single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.250 inches first flange and 1.256 inches first flange

Flange Inside Height:

0.617 inches first flange and 0.623 inches first flange

Flange Outside Width:

1.860 inches second flange and 1.890 inches second flange

Flange Outside Height:

1.860 inches second flange and 1.890 inches second flange

Flange Depth:

0.610 inches second flange and 0.640 inches second flange

Flange Connecting Hole Diameter:

0.164 inches first flange all connection facilities and 0.174 inches first flange all connection facilities

Voltage Standing Wave Ratio:

1.12

Insertion Loss In Decibels:

0.10

Maximum Operating Pressure:

25.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

Thread Size:

0.164 inches second flange all connection facilities

Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

NSN 5985-01-334-6741 Waveguide Assembly - Page 2 of 2



Waveguide Longer Offset Distance:
7.440 inches
Flange Connecting Facility And Quantity:
4 unthreaded hole first flange all connection facilities
Flange Style:
Cover type first flange
Waveguide Offset Distance:
1.560 inches
Flexibility:
Flexible single tubing segment
Material:
Aluminum alloy all tubing segment and flange
Surface Treatment:
Paint all tubing segment and flange outside surfaces
Style Designator:
Bend type
Supplementary Features:
Frequency 8.49 to 9.61 ghz
Thread Series Designator:
Unc second flange all connection facilities
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Filg:
A073a0