## NSN 5985-01-336-3058

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-336-3058

Application Design:
Transmission line
Body Material:
Metal
Body Style:
Rectangular, terminal/terminals on one surface
Body Surface Treatment:
Any acceptable
Overall Length:
0.500 inches
Overall Height:
0.380 inches
Overall Width:
0.230 inches
Body Height:
0.255 inches
Operating Tempurature Range:
-55.0/+100.0 degrees celsius
End Application:
6625-01-259-1060 analyzer, spectrum
Voltage Standing Wave Ratio:
1.50
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Power Rating:
0.5 watts average
Rf Signal Attenuation In Decibels:
2.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+1.5 gigahertz
Center To Center Distance Between First And Second Terminals:
0.100 inches
Center To Center Distance Between Second And Third Terminals:
0.100 inches
Center To Center Distance Between Third And Fourth Terminals:
0.100 inches
Attenuation Accuracy Reference Frequency:
1.5 gigahertz
Attenuation Accuracy In Decibels:

-0.20/+0.20

## NSN 5985-01-336-3058

Fixed Attenuator - Page 2 of 2



Mounting Method:
Terminal
Terminal Type And Quantity:
8 wire lead
Frequency Range:
Between 0.000 hertz and 1.500 gigahertz
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A20000