NSN 5985-01-336-3176

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-336-3176

Application Design:
Transmission line
Body Material:
Any acceptable
Body Style:
1b round, terminal/terminals in opposite surface
Terminal Material:
Any acceptable
Terminal Surface Treatment:
Any acceptable
Body Surface Treatment:
Any acceptable
Overall Length:
1.220 inches
Overall Diameter:
Between 0.350 inches and 0.385 inches
Operating Tempurature Range:
-65.0/+105.0 degrees celsius
Voltage Standing Wave Ratio:
1.15 and 1.30 and 1.40
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average and 0.2 kilowatts peak
Rf Signal Attenuation In Decibels:
0.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+11.4 gigahertz and +12.4/+18.0 gigahertz
Attenuation Accuracy Reference Frequency:
8.0 gigahertz
Attenuation Accuracy In Decibels:
-0.40/+0.40
Connection Type Per Function:
Female input and male output
Unpackaged Unit Weight:
0.500 ounces
Mounting Method:

Connector

NSN 5985-01-336-3176 Fixed Attenuator - Page 2 of 2



Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A20000