## NSN 5985-01-336-5523

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-336-5523

Application Design:
Transmission line
Body Style:
Irregular
Overall Length:
13.210 inches
Overall Height:
0.900 inches
Overall Width:
2.000 inches
Distance Between Mounting Facility Centers:
4.084 inches
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0/+70.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
7
Attenuation Per Step In Decibels:
10.0
Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:
Between 0.000 hertz and 22.000 gigahertz
Segment Attenuation Range In Decibels:
+0.00/+10.00 and $+10.00/+20.00$ and $+20.00/+30.00$ and $+30.00/+40.00$ and $+40.00/+50.00$ and $+50.00/+60.00$ and $+60.00/+70.00$
Mounting Thread Quantity:
40 per inch
Adjustment Device Type And Quantity:
1 electronic, programmable
Mounting Facility Pattern:
Two position in-line
Mounting Facility Screw Thread Diameter:
0.112 inches

**Supplementary Features:** Item is not field repairable

## NSN 5985-01-336-5523

Variable Attenuator - Page 2 of 2



## **Terminal Type And Quantity:**

3 connector, coaxial, female

**Fsc Application Data:** 

Antennas, waveguides, and related equip.

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A223a0