## NSN 5985-01-339-4275

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-339-4275

#### Application Design:

Transmission line

#### **Body Material:**

Brass

## Body Style:

Err-090

#### **Overall Length:**

1.030 inches

#### **Overall Diameter:**

0.317 inches

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Voltage Standing Wave Ratio:

1.15

#### Input Impedance Rating In Ohms:

50.0

#### **Output Impedance Rating In Ohms:**

50.0

#### **Coaxial Connector Series Designation:**

Sma

#### **Power Rating:**

2.0 watts average and 500.0 watts peak

#### **Rf Signal Attenuation In Decibels:**

13.0

#### Voltage Standing Wave Ratio Frequency Range:

+0.0/+18.0 gigahertz

#### Attenuation Accuracy In Decibels:

-0.15/+0.15

#### **Connection Type Per Function:**

Female input and male output

#### **Mounting Method:**

Connector

#### **Terminal Type And Quantity:**

2 connector

#### **Frequency Range:**

Between 0.000 hertz and 18.000 gigahertz

#### **Test Data Document:**

81349-mil-a-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-a-3933/25 government specification

### Shelf Life:

N/a

# NSN 5985-01-339-4275

Fixed Attenuator - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A20000

